

ACT-BEETLE99A/2812D-2M

Full HD

1920x1080

1080P 4-IN-1 VANDAL-PROOF CAMERA (AHD/HD-CVI/TVI/ANALOGUE)



1080P

OUTPUT



DWDR



OLUX

Features:

- 1/2.9" 2MP SONY Exmor CMOS
- High rate, long-distance, real-time transmission
- Defog, WDR, Auto Focus
- Motion detection, privacy mask
- 2.8-12mm lens, ICR MODULE
- 15-20M IR distance
- AHD/HD-CVI/TVI/Analogue 4-in-1 video output
- Vandal-proof, IP66, DC12V

**POWER
VIEW**

Specifications:

MODEL	ACT-BEETLE99A/2812D-2M
CAMERA	
Sensor	1/2.9" SONY 2M Exmor CMOS
Effective pixels	1920 (H)*1080 (V)
Resolution	2M, 1080P
Min. Illumination	0 Lux (IR ON)
Sync System	Internal
Scan System	Interlace
Lens	2.8-12mm 2M ICR Lens
Electronic Shutter	AUTO, Manual (X30~1/ 50000), FLK
S/N Rate	≥50db (AGC OFF)
Video output	Digital: AHD/HD-CVI/TVI Analog: 1Vp-p Composite Output(75Ω/BNC)
OSD MENU	
White balance	ATW/AWC-SET/INDOOR/OUTDOOR/MANUAL/AWB
NR	2DNR/3DNR,OFF
Image adjustable	lightness, contrast, sharpness, AGC
DWDR	ON/ OFF
BLC	BLC/ HLC/ OFF
AGC	ON/ OFF/ AUTO(1-15)
TDN THRESHOLD	B/W , COLOR, AUTO
Privacy mask	OFF/ ON (4 area)
Motion detection	OFF/ ON (4 area)
Mirror	horizontal/ vertical/ HV mirror
Sens-up	OFF/ON(X30,X25,X20,X15,X10,X8,X6,X4,X2)
Lens shading	OFF/ ON

compensation	
Healing function	Manual/ AUTO
Defog	OFF/ ON
OSD menu	Chinese, english etc 12 languages
GENERAL	
Transmission	75-3/300m,75-5/500m
IR Distance	15-20M(18xΦ5IR leds)
power supply	DC12V± 10%
Power(max)	260mA±10mA
Operating Temperature	-20°C ~ 55°C/ 0%-90%
Dimensions(mm)	112(H)*150(D)mm
Weight/PCS (g)	855g
Qty	12 pcs
Outer carton dimensions	510mm(L)*340mm(W)*300mm(H)
Attention: AHD/CVI/TVI/CVBS signal transform method: Press the OSD left key for 5 seconds, CVBS output; Press the OSD right key for 5 seconds, AHD output; Press the OSD button key for 5 seconds, CVI output; Press the OSD The NEXT key 5 seconds, TVI output	

Dimension:

