

CVI-HD24R60/2712-4M

4MP WDR IR EYEBALL DOME CAMERA



Features:

- 1/3" CMOS
- 2560x1440 Full 4MP HD real-time
- HD and CVBS dual-output
- 2.7-12mm motorized lens
- Max. 60M Smart IR
- IP67 rated
- DC12V



Specifications:

Model	CVI-HD24R60/2712-4M
CAMERA	
Image Sensor	1/3" CMOS
Effective Pixels	2688(H)×1520(V), 4.1MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/4s – 1/100,000s NTSC: 1/3s – 1/100,000s
Min. Illumination	0.01Lux/F1.3, 0Lux when IR ON
S/N Ratio	More than 65dB
IR Distance	UP to 60 Meter
IR On/Off Control	Auto/Manual
IR LEDs	2
Lens	
Lens Typs	Motorised lens/Fixed iris
Mount type	Board-in
Focal Length	2.7-12mm
Max. Aperture	F1.3
Angle of View	H: 98° - 26°
Focus Control	Auto/Manual
Close Focus Distance	200mm 7.87"
Pan/Tilt/Rotation	
Pan/Tilt/Rotation	Pan: 0°-360° Tilt: 0°-78° Rotation: 0°-360°
Video	
Resolution	4MP (2560x1440)
Frame Rate	25fps@4MP, 25/30fps@1080P, 25/30fps@720P
Video Output	Digital: HD-CVI ; Analog: 1Vp-p Composite Output(75Ω/BNC)
Day&Night	Auto/Manual
White Balance	Auto/Manual
BLC Mode	BLC/HLC/WDR
WDR	120dB
Gain Control	AGC
Noise Reduction	2D/3D
Smart IR	Auto/Manual
General	
Input Voltage	DC12V±25%
Power Consumption	Max. 8.4W
Weight & Dimension	590g, Φ122mmx104.9mm
IP Rating	IP67
Operating temperature	-30°C~ +60°C
Operation humidity	< 90%RH

Dimensions:

